


## PIPE SCREW JOINTS E STRAIGHT COUPLINGS

THE WORLD OF TUBE FITTINGS

### E STRAIGHT COUPLINGS



description	pipe OD	PN series	S	S <sub>1</sub>	L <sub>1</sub>	l <sub>1</sub>	kg % pc
E 4-LL	4	LL 100 (400)	9	10	31	12	1.4
E 6-LL	6	LL 100 (400)	11	12	32	9	2.1
E 8-LL	8	LL 100 (400)	12	14	35	12	2.6
DS-E 6-L	6	L 500 (2200)	12	14	39	10	3.5
DS-E 8-L	8	L 500 (2200)	14	17	40	11	4.9
DS-E 10-L	10	L 500 (2200)	17	19	42	13	6.9
DS-E 12-L	12	400 (1700)	19	22	43	14	8.5
DS-E 15-L	15	400 (1700)	24	27	46	16	13.8
DS-E 18-L	18	400 (1700)	27	32	48	16	19.5
DS-E 22-L	22	250 (1100)	32	36	52	20	26.2
DS-E 28-L	28	250 (1100)	41	41	54	21	31.5
DS-E 35-L	35	250 (1100)	46	50	63	20	49.4
DS-E 42-L	42	250 (1100)	55	60	66	21	72.8
DS-E 6-S	6	S 800 (3400)	14	17	45	16	5.9
DS-E 8-S	8	S 800 (3400)	17	19	47	18	7.8
DS-E 10-S	10	S 800 (3400)	19	22	49	17	11.0
DS-E 12-S	12	630 (2700)	22	24	51	19	13.6
DS-E 14-S	14	630 (2700)	24	27	57	22	18.2
DS-E 16-S	16	630 (2700)	27	30	57	21	22.3
DS-E 20-S	20	400 (1700)	32	36	66	23	34.7
DS-E 25-S	25	400 (1700)	41	46	74	26	66.9
DS-E 30-S	30	400 (1700)	46	50	80	27	80.9
DS-E 38-S	38	400 (1700)	55	60	90	29	119.4

*L<sub>1</sub> = approximate length with nut tightened*

*Please see "Engineering and technical data - Selecting the correct tube fitting" for more information on pressure.*