


PIPE SCREW JOINTS ER STRAIGHT REDUCING COUPLINGS

ER STRAIGHT REDUCING COUPLINGS



description	pipe OD ₁	Pipe OD ₂	PN series	S	S ₁	S ₂	L ₁	L ₁	kg % pc
ER 6/4-LL	6	4	LL 100 (400)	11	10	12	32	10.5	1.8
ER 8/4-LL	8	4	LL 100 (400)	12	10	14	34	12.5	2.1
ER 8/6-LL	8	6	LL 100 (400)	12	12	14	34	11.0	2.3
DS-ER 8/6-L	8	6	L 500 (2200)	14	14	17	40	11.0	4.3
DS-ER 10/6-L	10	6	L 500 (2200)	17	14	19	41	12.0	5.2
DS-ER 10/8-L	10	8	L 500 (2200)	17	17	19	41	12.0	5.7
DS-ER 12/6-L	12	6	L 400 (1700)	19	14	22	42	13.0	6.5
DS-ER 12/8-L	12	8	L 400 (1700)	19	17	22	42	13.0	7.0
DS-ER 12/10-L	12	10	L 400 (1700)	19	19	22	43	14.0	7.5
DS-ER 15/10-L	15	10	L 400 (1700)	24	19	27	45	15.0	10.7
DS-ER 15/12-L	15	12	L 400 (1700)	24	22	27	45	15.0	11.4
DS-ER 18/10-L	18	10	L 400 (1700)	27	19	32	46	15.5	14.3
DS-ER 18/12-L	18	12	L 400 (1700)	27	22	32	46	15.5	15.0
DS-ER 18/15-L	18	15	L 400 (1700)	27	27	32	48	16.5	17.2
DS-ER 22/12-L	22	12	L 250 (1100)	32	22	36	48	17.5	19.3
DS-ER 22/15-L	22	15	L 250 (1100)	32	27	36	50	18.5	21.8
DS-ER 22/18-L	22	18	L 250 (1100)	32	32	36	50	18.0	23.8
DS-ER 28/18-L	28	18	L 250 (1100)	41	32	41	52	19.0	30.6
DS-ER 28/22-L	28	22	L 250 (1100)	41	36	41	54	21.0	32.6
DS-ER 35/22-L	35	22	L 250 (1100)	46	36	50	59	21.0	44.3
DS-ER 35/28-L	35	28	L 250 (1100)	46	41	50	59	21.0	46.1
DS-ER 8/6-S	8	6	S 800 (3400)	17	17	19	47	18.0	7.4
DS-ER 10/6-S	10	6	S 800 (3400)	19	17	22	48	17.5	9.1
DS-ER 10/8-S	10	8	S 800 (3400)	19	19	22	48	17.5	9.5
DS-ER 12/6-S	12	6	S 630 (2700)	22	17	24	50	19.5	11.1
DS-ER 12/8-S	12	8	S 630 (2700)	22	19	24	50	19.5	11.5
DS-ER 12/10-S	12	10	S 630 (2700)	22	22	24	51	19.0	12.7
DS-ER 14/10-S	14	10	S 630 (2700)	24	22	27	54	20.5	15.6
DS-ER 14/12-S	14	12	S 630 (2700)	24	24	27	54	20.5	16.2
DS-ER 16/12-S	16	12	S 630 (2700)	27	24	30	54	20.0	18.8
DS-ER 16/14-S	16	14	S 630 (2700)	27	27	30	57	21.5	21.2
DS-ER 20/10-S	20	10	S 400 (1700)	32	22	36	60	22.0	27.1
DS-ER 20/12-S	20	12	S 400 (1700)	32	24	36	60	22.0	27.7
DS-ER 20/16-S	20	16	S 400 (1700)	32	30	36	63	23.0	31.3
DS-ER 25/16-S	25	16	S 400 (1700)	41	30	46	68	25.5	51.2
DS-ER 25/20-S	25	20	S 400 (1700)	41	36	46	71	25.5	56.4
DS-ER 30/20-S	30	20	S 400 (1700)	46	36	50	74	26.0	65.1
DS-ER 30/25-S	30	25	S 400 (1700)	46	46	50	77	26.5	77.8
DS-ER 38/30-S	38	30	S 400 (1700)	55	50	60	87	29.5	110.3

L₁ = approximate length with nut tightened

Please see "Engineering and technical data - Selecting the correct tube fitting" for more information on pressure.