

LOL Plus Lock-On Hose Low Pressure

HOSE

Black Cover Only Meets Flame Resistance Acceptance Designation "MSHA 2G".

Recommended For: Petroleum-base hydraulic oils, water, glycol antifreeze solutions, engine lubricating oils, and air. Lock-On hose and couplings are NOT recommended for pressure surge applications or critical applications, such as permanent piping in residential or commercial buildings. Do not use for gasoline or diesel fuels, unless approved by Gates H/C Product Application.

Tube: Black, oil resistant, synthetic rubber highly resistant to oil and heat (Nitrile - Type C). See Hose Stock Characteristics.

Reinforcement: One fiber braid.

Cover: Oil and abrasion resistant synthetic rubber (Modified Nitrile - Type C2). Available in black Neoprene (LOLA), blue (LOLB), green (LOLG), red (LOLR), yellow (LOLY) and gray (LOLC) colors.

Temperature Range: -40°F to +212°F (-40°C to +100°C). Air to +160°F (+71°C) only. For water emulsions see Temperature Limits Table.

Coupling Recommendation (See gates.com/ecrimp or Crimp Data Manual 35019)

Field Attachable LOC Couplings (Section J)

GLP Couplings (except -3) (Section J)

Use clamp over beaded nipple.



Description	Product No.							Standard Pack	Weight (Lbs.)
3LOLAXREEL*	3284-2500	3/16	.41	300	1200	3.0	28	300	.07
3LOLBXREEL*	3284-2510	3/16	.41	300	1200	3.0	28	300	.07
3LOLCXREEL***	3284-2520	3/16	.41	300	1200	3.0	28	300	.07
3LOLGXREEL***	3284-2530	3/16	.41	300	1200	3.0	28	300	.07
3LOLRXREEL*	3284-2540	3/16	.41	300	1200	3.0	28	300	.07
3LOLYXREEL***	3284-2560	3/16	.41	300	1200	3.0	28	300	.07
4LOLA X50FT	3284-2266	1/4	.47	300	1200	3.0	28	1	3.99
4LOLAXREEL	3284-2501	1/4	.47	300	1200	3.0	28	475	.08
4LOLB X25FT	3284-2272	1/4	.47	300	1200	3.0	28	1	1.96
4LOLBXREEL	3284-2511	1/4	.47	300	1200	3.0	28	475	.08
4LOLCXREEL	3284-2521	1/4	.47	300	1200	3.0	28	475	.08
4LOLG X25FT	3284-2277	1/4	.47	300	1200	3.0	28	1	1.97
4LOLGXREEL	3284-2531	1/4	.47	300	1200	3.0	28	475	.08
4LOLR X25FT	3284-2281	1/4	.47	300	1200	3.0	28	1	1.97
4LOLRXREEL	3284-2541	1/4	.47	300	1200	3.0	28	475	.08
4LOLYXREEL	3284-2561	1/4	.47	300	1200	3.0	28	475	.08
5LOLA X25FT	3284-2297	5/16	.55	300	1200	3.0	28	1	2.57
5LOLA X50FT	3284-2267	5/16	.55	300	1200	3.0	28	1	5.13
5LOLAXREEL	3284-2502	5/16	.55	300	1200	3.0	28	300	.10
6LOLA X50FT	3284-2268	3/8	.63	300	1200	3.0	28	1	6.36
6LOLAXREEL	3284-2503	3/8	.63	300	1200	3.0	28	300	.13
6LOLB X25FT	3284-2273	3/8	.63	300	1200	3.0	28	1	3.12
6LOLBXREEL	3284-2513	3/8	.63	300	1200	3.0	28	300	.13
6LOLCXREEL	3284-2523	3/8	.63	300	1200	3.0	28	300	.13
6LOLG X25FT	3284-2278	3/8	.63	300	1200	3.0	28	1	3.14
6LOLGXREEL	3284-2533	3/8	.63	300	1200	3.0	28	300	.13
6LOLR X25FT	3284-2282	3/8	.63	300	1200	3.0	28	1	3.14
6LOLRXREEL	3284-2543	3/8	.63	300	1200	3.0	28	300	.13
6LOLYXREEL	3284-2563	3/8	.63	300	1200	3.0	28	300	.13
8LOLA X50FT	3284-2269	1/2	.77	300	1200	5.0	28	1	8.55
8LOLAXREEL	3284-2504	1/2	.77	300	1200	5.0	28	300	.17
8LOLB X25FT	3284-2274	1/2	.77	300	1200	5.0	28	1	4.19
8LOLBXREEL	3284-2515	1/2	.77	300	1200	5.0	28	300	.17
8LOLCXREEL	3284-2525	1/2	.77	300	1200	5.0	28	300	.17
8LOLG X25FT	3284-2279	1/2	.77	300	1200	5.0	28	1	4.21
8LOLGXREEL	3284-2535	1/2	.77	300	1200	5.0	28	300	.17
8LOLR X25FT	3284-2283	1/2	.77	300	1200	5.0	28	1	4.21
8LOLRXREEL	3284-2545	1/2	.77	300	1200	5.0	28	300	.17
8LOLYXREEL	3284-2565	1/2	.77	300	1200	5.0	28	300	.17

*Couplings for this size are available on special order only.







**Special hose, subject to minimum order requirements if not in inventory.

NOTE: LOL Lock-On Hose is packaged in UPS shippable reels.

NOTE: The use of clamps with LOC Couplings is not recommended.

LOL Plus Lock-On Hose Low Pressure

Continued

Description	Product No.							Standard Pack	Weight (Lbs.)
10LOLA X50FT	3284-2270	5/8	.94	300	1200	6.0	28	1	12.10
10LOLAXREEL	3284-2505	5/8	.94	300	1200	6.0	28	250	.23
10LOLB X25FT	3284-2275	5/8	.94	300	1200	6.0	28	1	5.95
10LOLBXREEL	3284-2517	5/8	.94	300	1200	6.0	28	250	.23
10LOLCXREEL	3284-2527	5/8	.94	300	1200	6.0	28	250	.23
10LOLGXREEL*	3284-2537	5/8	.94	300	1200	6.0	28	250	.23
10LOLRXREEL*	3284-2547	5/8	.94	300	1200	6.0	28	250	.23
10LOLYXREEL*	3284-2567	5/8	.94	300	1200	6.0	28	250	.23
12LOLA X50FT	3284-2271	3/4	1.06	300	1200	7.0	15	1	13.93
12LOLAXREEL	3284-2506	3/4	1.06	300	1200	7.0	15	225	.28
12LOLB X25FT	3284-2276	3/4	1.06	300	1200	7.0	15	1	6.85
12LOLBXREEL	3284-2519	3/4	1.06	300	1200	7.0	15	225	.28
12LOLCXREEL	3284-2529	3/4	1.06	300	1200	7.0	15	225	.28
12LOLG X25FT	3284-2280	3/4	1.06	300	1200	7.0	15	1	6.87
12LOLGXREEL	3284-2536	3/4	1.06	300	1200	7.0	15	225	.28
12LOLR X25FT	3284-2284	3/4	1.06	300	1200	7.0	15	1	6.87
12LOLRXREEL	3284-2549	3/4	1.06	300	1200	7.0	15	225	.28
12LOLYXREEL	3284-2569	3/4	1.06	300	1200	7.0	15	225	.28

*Special hose, subject to minimum order requirements if not in inventory.

NOTE: LOL Lock-On Hose is packaged in UPS shippable reels.

NOTE: The use of clamps with LOC Couplings is not recommended.

HOSE

HOSE/CPLG.
SELECTION

G8K COUPLINGS

GLOBALSPIRAL
COUPLINGS

PCM / PCS
FERRULES

MEGACRIMP
COUPLINGS

STAINLESS
STEEL

POWER CRIMP
COUPLINGS

LOC, GL AND GLP
COUPLINGS

POLARSEAL
COUPLINGS

POLARSEAL II
COUPLINGS

C14 COUPLINGS

PCTS
THERMOPLASTIC
COUPLINGS

FIELD
ATTACHABLE G1
& G2 COUPLINGS

FIELD
ATTACHABLE C5
& C5E
COUPLINGS

SURELOK AIR
BRAKE
COUPLINGS

ADAPTERS

QUICK
DISCONNECT
COUPLERS

LIVE SWIVEL

BALL VALVES

ACCESSORIES

EQUIPMENT AND
PARTS

NOTE: Federal law requires registration with the Department of Transportation for anyone producing air brake hose assemblies with swaged or crimped fittings. See Engineering and Technical Data Section for compliance.