

CERAMIC HOSE

CEMD

Product Specifications

Application : Designed for metal castings, steel, stone and wherever abrasive products transfer discharge service.

Tube : Black abrasion NR/SBR rubber and ceramic ball

Reinforcement : Spiral-plyed synthetic fabric

Cover : Black abrasion, weather & ozone resistant synthetic rubber

튜브 : 검정색 내마모 NR/SBR 브랜딩 합성고무 & 세라믹 볼

보강층 : 고강도 합성섬유 스파이럴 성형

커버 : 검정색 내마모, 내후, 내오존성 합성고무

Temperature (온도)	-20°F to 212°F (-30°C to 80°C)		
Safety Factor (안전율)	4:1	Max. Lengths (최대 길이)	66FT / 20m
Branding (브랜딩)	HWASEUNG Exwill CERAMIC HOSE 10K MAX. W.P		

Part No.	I.D		O.D		MAX. W.P		Bend Radius		Approx. Weight	
	in	mm	in	mm	psi	bar	in	mm	lbs/ft	kg/m
CEMD										
CEMD-132	1 1/4"	31.8	2.18	55.4	150	10	-	-	1.75	2.60
CEMD-152	1 1/2"	38.1	2.43	61.7	150	10	-	-	2.22	3.30
CEMD-202	2"	50.8	2.97	75.4	150	10	-	-	3.16	4.70
CEMD-252	2 1/2"	63.5	3.47	88.1	150	10	-	-	3.76	5.60
CEMD-302	3"	76.2	4.01	101.8	150	10	-	-	4.43	6.60
CEMD-404	4"	101.6	5.06	128.6	150	10	-	-	5.85	8.70

CERAMIC SUCTION & DISCHARGE HOSE

CEMS

Product Specifications

Application : Designed for metal castings, steel, stone and wherever abrasive products transfer suction & discharge service.

Tube : Black abrasion NR/SBR rubber and ceramic ball

Reinforcement : Spiral-plyed synthetic fabric with helix wire

Cover : Black abrasion, weather & ozone resistant synthetic rubber

튜브 : 검정색 내마모 NR/SBR 브랜딩 합성고무 & 세라믹 볼

보강층 : 고강도 합성섬유 스파이럴 성형 & 경강선 나선형 성형

커버 : 검정색 내마모, 내후, 내오존성 합성고무

Temperature (온도)	-20°F to 212°F (-30°C to 80°C)		
Safety Factor (안전율)	4:1	Max. Lengths (최대 길이)	66FT / 20m
Branding (브랜딩)	HWASEUNG Exwill CERAMIC SUCTION & DISCHARGE HOSE 10K MAX. W.P		

Part No.	I.D		O.D		MAX. W.P		Bend Radius		Approx. Weight	
	in	mm	in	mm	psi	bar	in	mm	lbs/ft	kg/m
CEMS										
CEMS-152	1 1/2"	38.1	2.56	65.0	150	10	12	300	2.69	4.00
CEMS-202	2"	50.8	3.15	80.0	150	10	16	400	3.76	5.60
CEMS-252	2 1/2"	63.5	3.58	91.0	150	10	20	500	4.64	6.90
CEMS-302	3"	76.2	4.09	104.0	150	10	24	600	5.38	8.00
CEMS-404	4"	101.6	5.28	134.0	150	10	32	800	6.85	10.20