

OIL DISCHARGE HOSE

OD20DBK / OD20DRD
OD30DBK / OD50DBK

Product Specifications

Application : The softwall hose is for the discharge of gasoline, oil and other petroleum based products on tank and docks.

Tube : Nitrile synthetic rubber RMA class A (High oil resistance)

Reinforcement : Spiral-plied synthetic fabric with static wire

Cover : Black (or Red) abrasion, oil, weather & ozone resistant Neoprene rubber

Temperature	-20°F to 180°F (-30°C to 80°C)
Safety Factor	4:1
Max. Lengths	200FT(1" ~ 6"), 100FT(8") / 60m(1" ~ 6"), 30m(8")
Branding	HWASEUNG Exwill PETROLEUM DISCHARGE - - PSI MAX. W.P



Part No.	I.D		O.D		MAX. W.P		Bend Radius		Approx. Weight	
	in	mm	in	mm	psi	bar	in	mm	lbs/ft	kg/m
OD20DBK (Black) / OD20DRD (Red)										
OD20DBK/OD20DRD-102	1"	25.4	1.42	36.0	200	14	10	250	0.47	0.70
OD20DBK/OD20DRD-132	1 1/4"	31.8	1.67	42.4	200	14	13	330	0.56	0.83
OD20DBK/OD20DRD-152	1 1/2"	38.1	1.96	49.9	200	14	15	380	0.65	0.97
OD20DBK/OD20DRD-202	2"	50.8	2.46	62.6	200	14	20	500	0.95	1.41
OD20DBK/OD20DRD-252	2 1/2"	63.5	2.96	75.3	200	14	25	650	1.15	1.71
OD20DBK/OD20DRD-304	3"	76.2	3.56	90.3	200	14	30	750	1.59	2.37
OD20DBK/OD20DRD-404	4"	101.6	4.64	117.8	200	14	40	1,000	2.47	3.68
OD20DBK/OD20DRD-504	5"	127.0	5.64	143.2	200	14	50	1,300	3.04	4.52
OD20DBK/OD20DRD-606	6"	152.4	6.75	171.4	200	14	60	1,500	4.23	6.30
OD20DBK/OD20DRD-806	8"	203.2	8.75	222.2	200	14	80	2,000	5.55	8.26
OD30DBK (Black)										
OD30DBK-202	2"	50.8	2.48	63.0	300	20	20	500	0.98	1.46
OD30DBK-304	3"	76.2	3.59	91.2	300	20	30	750	1.75	2.60
OD30DBK-404	4"	101.6	4.73	120.2	300	20	40	1,000	2.85	4.24
OD30DBK-504	5"	127.0	5.73	145.6	300	20	50	1,300	3.49	5.19
OD30DBK-606	6"	152.4	6.84	173.8	300	20	60	1,500	4.77	7.10
OD50DBK (Black)										
OD50DBK-204	2"	50.8	2.56	65.0	500	35	20	500	1.16	1.72
OD50DBK-306	3"	76.2	3.67	93.2	500	35	30	750	2.00	2.97
OD50DBK-408	4"	101.6	4.78	121.4	500	35	40	1,000	3.03	4.51
OD50DBK-508	5"	127.0	5.78	146.8	500	35	50	1,300	3.71	5.52
OD50DBK-610	6"	152.4	6.91	175.4	500	35	60	1,500	5.13	7.64