

POTABLE WATER SUCTION HOSE

PWS15

Product Specifications

Application : Designed to handle water suitable for drinking.
This hose is not NSF approved.

Tube : White NR/SBR synthetic rubber

Reinforcement : Spiral-plyed synthetic fabric with dual helix wire

Cover : Blue abrasion, weather & ozone resistant synthetic rubber (Smooth cover)

Temperature	-20°F to 180°F (-30°C to 80°C)		
Safety Factor	4:1	Max. Lengths	200FT / 60m
Vacuum	737mmHg / 29inHg		
Branding	HWASEUNG Exwill POTABLE WATER SUCTION 150PSI MAX. W.P		



Part No.	I.D.		O.D.		MAX. W.P.		Bend Radius		Approx. Weight	
	in	mm	in	mm	psi	bar	in	mm	lbs/ft	kg/m
PWS15										
PWS15-152	1 1/2"	38.1	2.03	51.5	150	10	10	250	1.03	1.54
PWS15-202	2"	50.8	2.57	65.4	150	10	12	300	1.44	2.15
PWS15-252	2 1/2"	63.5	3.07	78.1	150	10	16	400	1.75	2.60
PWS15-302	3"	76.2	3.62	92.0	150	10	20	500	2.43	3.61
PWS15-402	4"	101.6	4.62	117.4	150	10	28	700	3.15	4.69

POTABLE WATER DISCHARGE HOSE

PWD15

Product Specifications

Application : Designed to handle water suitable for drinking.
This hose is not NSF approved. Used in discharge service only.

Tube : White NR/SBR synthetic rubber

Reinforcement : Spiral-plyed synthetic fabric

Cover : Black abrasion, weather & ozone resistant synthetic rubber (Smooth cover)

Temperature	-20°F to 180°F (-30°C to 80°C)		
Safety Factor	4:1	Max. Lengths	200FT / 60m
Branding	HWASEUNG Exwill POTABLE WATER DISCHARGE 150PSI MAX. W.P		



Part No.	I.D.		O.D.		MAX. W.P.		Bend Radius		Approx. Weight	
	in	mm	in	mm	psi	bar	in	mm	lbs/ft	kg/m
PWD15										
PWD15-252	2 1/2"	63.5	3.05	77.5	150	10	25	650	1.46	2.17
PWD15-304	3"	76.2	3.65	92.6	150	10	30	750	1.98	2.94
PWD15-404	4"	101.6	4.65	118.0	150	10	40	1,000	2.56	3.81