

## Double Bolt Clamps

### Features:

- inner surface has dual gripping ridges
- bolt lugs are reinforced to prevent bending out of alignment
- Torque values for clamps are based on dry bolts.
- The use of lubricant on bolts will adversely effect clamp performance.
- measure hose OD accurately before ordering clamps
- Consult Dixon™ when using double bolt clamps on helical wire hose.



without saddles



with saddles

Hose OD		Plated Iron		Opt Qty	Torque in ft. lbs.
from	to	Part #			
1-8/64"	1-12/64"	<b>J48</b>		100	15
1-12/64"	1-24/64"	<b>J49</b>		50	21
1-28/64"	1-34/64"	<b>JX49</b>		25	21
1-40/64"	1-52/64"	<b>DL14</b>		25	40
1-48/64"	2-3/64"	<b>DL20</b>		25	27
2-7/64"	2-19/64"	<b>DL24</b> <sup>1</sup>		25	27
2-20/64"	2-40/64"	<b>DL32</b> <sup>1</sup>		25	40
2-32/64"	2-48/64"	<b>DL275</b>		25	40
2-48/64"	3-4/64"	<b>DL306</b>		20	60
3-4/64"	3-24/64"	<b>DL328</b>		20	60
3-16/64"	3-32/64"	<b>DL350</b>		20	60

<sup>1</sup> investment cast carbon steel

Hose OD		Plated Iron		Opt Qty	Torque in ft. lbs.
from	to	Part #			
3-32/64"	3-52/64"	<b>400</b>		25	40
3-50/64"	4-4/64"	<b>431</b>		20	40
4-2/64"	4-18/64"	<b>463</b>		20	40
4-16/64"	4-60/64"	<b>525</b>		10	60
4-32/64"	5-16/64"	<b>550</b>		10	60
5-8/64"	5-44/64"	<b>600</b>		10	60
5-44/64"	5-60/64"	<b>639</b>		10	60
5-60/64"	6-32/64"	<b>675</b>		10	60
6-32/64"	7-36/64"	<b>769</b>		10	60
7-44/64"	8-12/64"	<b>818</b>		5	125
8-16/64"	8-56/64"	<b>875</b>		5	125
8-60/64"	9-56/64"	<b>988</b>		5	125
9-60/64"	11-24/64"	<b>1125</b>		5	125
11-12/64"	13"	<b>1275</b>		3	125
12-12/64"	14"	<b>1360</b>		2	200
13-12/64"	15"	<b>1450</b>		2	200
15-4/64"	17-32/64"	<b>1700</b>		2	260

K