


PIPE CONNECTIONS REDUCING CONNECTIONS

THE WORLD OF TUBE FITTINGS

RLDKO REDUCING CONNECTION WITH TAPER

With taper and O-ring according to DIN 3865.

Supplied with fitted NBR O-ring (e.g. Perbunan),
FPM O-ring (e.g. Viton) upon request.



description	pipe OD1	pipe OD2	PN series	L	l	S	S ₁	S ₂	d ₁	O-ring	kg % pc
DS-RLDKO 8/6	8	6	L 500 (2200)	38.0	23.5	12	14	17	M 14x1.5	6x1.5	3.9
DS-RLDKO 10/6	10	6	L 500 (2200)	39.5	25.0	14	14	19	M 16x1.5	7.5x1.5	4.9
DS-RLDKO 10/8	10	8	L 500 (2200)	39.5	25.0	14	17	19	M 16x1.5	7.5x1.5	5.3
DS-RLDKO 12/6	12	6	L 400 (1700)	39.5	25.0	17	14	22	M 18x1.5	9x1.5	6.3
DS-RLDKO 12/8	12	8	L 400 (1700)	39.5	25.0	17	17	22	M 18x1.5	9x1.5	6.8
DS-RLDKO 12/10	12	10	L 400 (1700)	40.5	26.0	17	19	22	M 18x1.5	9x1.5	7.0
DS-RLDKO 15/6	15	6	L 400 (1700)	43.5	29.0	22	14	27	M 22x1.5	12x2	5.5
DS-RLDKO 15/8	15	8	L 400 (1700)	43.5	29.0	22	17	27	M 22x1.5	12x2	9.8
DS-RLDKO 15/10	15	10	L 400 (1700)	44.0	29.5	22	19	27	M 22x1.5	12x2	10.7
DS-RLDKO 15/12	15	12	L 400 (1700)	44.0	29.5	22	22	27	M 22x1.5	12x2	11.0
DS-RLDKO 18/6	18	6	L 400 (1700)	42.5	28.0	24	14	32	M 26x1.5	15x2	11.9
DS-RLDKO 18/8	18	8	L 400 (1700)	42.5	28.0	24	17	32	M 26x1.5	15x2	12.4
DS-RLDKO 18/10	18	10	L 400 (1700)	43.5	29.0	24	19	32	M 26x1.5	15x2	12.8
DS-RLDKO 18/12	18	12	L 400 (1700)	43.5	29.0	24	22	32	M 26x1.5	15x2	17.2
DS-RLDKO 18/15	18	15	L 400 (1700)	45.0	30.0	24	27	32	M 26x1.5	15x2	19.0
DS-RLDKO 22/6	22	6	L 250 (1100)	46.5	32.0	27	14	36	M 30x2	20x2	16.9
DS-RLDKO 22/8	22	8	L 250 (1100)	46.5	32.0	27	17	36	M 30x2	20x2	17.6
DS-RLDKO 22/10	22	10	L 250 (1100)	47.5	33.0	27	19	36	M 30x2	20x2	17.8
DS-RLDKO 22/12	22	12	L 250 (1100)	47.5	33.0	27	22	36	M 30x2	20x2	18.6
DS-RLDKO 22/15	22	15	L 250 (1100)	49.0	34.0	27	27	36	M 30x2	20x2	20.8
DS-RLDKO 22/18	22	18	L 250 (1100)	49.5	33.5	27	32	36	M 30x2	20x2	24.4
DS-RLDKO 28/6	28	6	L 250 (1100)	48.5	34.0	36	14	41	M 36x2	26x2	29.3
DS-RLDKO 28/8	28	8	L 250 (1100)	48.5	34.0	36	17	41	M 36x2	26x2	29.3
DS-RLDKO 28/10	28	10	L 250 (1100)	49.5	35.0	36	19	41	M 36x2	26x2	29.9
DS-RLDKO 28/12	28	12	L 250 (1100)	49.5	35.0	36	22	41	M 36x2	26x2	30.8
DS-RLDKO 28/15	28	15	L 250 (1100)	51.0	36.0	36	27	41	M 36x2	26x2	33.0
DS-RLDKO 28/18	28	18	L 250 (1100)	51.5	35.5	36	32	41	M 36x2	26x2	38.3
DS-RLDKO 28/22	28	22	L 250 (1100)	53.5	37.5	36	36	41	M 36x2	26x2	39.1
DS-RLDKO 35/6	35	6	L 250 (1100)	51.5	37.0	46	14	50	M 45x2	32x2.5	33.2
DS-RLDKO 35/8	35	8	L 250 (1100)	51.5	37.0	46	17	50	M 45x2	32x2.5	33.7
DS-RLDKO 35/10	35	10	L 250 (1100)	52.5	38.0	46	19	50	M 45x2	32x2.5	34.2
DS-RLDKO 35/12	35	12	L 250 (1100)	52.5	38.0	46	22	50	M 45x2	32x2.5	35.3
DS-RLDKO 35/15	35	15	L 250 (1100)	54.0	39.0	46	27	50	M 45x2	32x2.5	37.1
DS-RLDKO 35/18	35	18	L 250 (1100)	54.5	38.5	46	32	50	M 45x2	32x2.5	39.1
DS-RLDKO 35/22	35	22	L 250 (1100)	56.5	40.5	46	36	50	M 45x2	32x2.5	41.6
DS-RLDKO 35/28	35	28	L 250 (1100)	57.0	40.5	46	41	50	M 45x2	32x2.5	42.6
DS-RLDKO 42/6	42	6	L 250 (1100)	52.0	37.5	50	14	60	M 52x2	38x2.5	51.2
DS-RLDKO 42/8	42	8	L 250 (1100)	52.0	37.5	50	17	60	M 52x2	38x2.5	51.8
DS-RLDKO 42/10	42	10	L 250 (1100)	56.0	41.5	50	19	60	M 52x2	38x2.5	52.3
DS-RLDKO 42/12	42	12	L 250 (1100)	56.0	41.5	50	22	60	M 52x2	38x2.5	53.4
DS-RLDKO 42/15	42	15	L 250 (1100)	57.5	42.5	50	27	60	M 52x2	38x2.5	55.1
DS-RLDKO 42/18	42	18	L 250 (1100)	58.0	42.0	50	32	60	M 52x2	38x2.5	60.7
DS-RLDKO 42/22	42	22	L 250 (1100)	60.0	44.0	50	36	60	M 52x2	38x2.5	66.5
DS-RLDKO 42/28	42	28	L 250 (1100)	60.5	44.0	50	41	60	M 52x2	38x2.5	68.0
DS-RLDKO 42/35	42	35	L 250 (1100)	64.5	43.0	50	50	60	M 52x2	38x2.5	69.5

L = approximate length, with nut tightened

Please see "Engineering and technical data - Selecting the correct tube fitting" for
- reducing example.

- more information on pressure.