


PIPE CONNECTIONS REDUCING CONNECTIONS

RSDKO REDUCING CONNECTION WITH TAPER

With taper and O-ring according to DIN 3865.

Supplied with fitted NBR O-ring (e.g. Perbunan),
FPM O-ring (e.g. Viton) upon request.



description	pipe OD1	pipe OD2	PN series	L	l	S	S ₁	S ₂	d ₁	O-ring	kg % pc
DS-RSDKO 8/6	8	6	S 800 [3400]	41.5	27.0	14	17	19	M 16x1.5	6x1.5	3.4
DS-RSDKO 10/6	10	6	S 800 [3400]	42.0	27.5	17	17	22	M 18x1.5	7.5x1.5	7.2
DS-RSDKO 10/8	10	8	S 800 [3400]	42.0	27.5	17	19	22	M 18x1.5	7.5x1.5	7.8
DS-RSDKO 12/6	12	6	S 630 [2700]	43.5	29.0	19	17	24	M 20x1.5	9x1.5	8.3
DS-RSDKO 12/8	12	8	S 630 [2700]	43.5	29.0	19	19	24	M 20x1.5	9x1.5	9.3
DS-RSDKO 12/10	12	10	S 630 [2700]	45.5	29.5	19	22	24	M 20x1.5	9x1.5	10.7
DS-RSDKO 14/6	14	6	S 630 [2700]	48.0	33.5	22	17	27	M 22x1.5	10x2	9.2
DS-RSDKO 14/8	14	8	S 630 [2700]	48.0	33.5	22	19	27	M 22x1.5	10x2	9.9
DS-RSDKO 14/10	14	10	S 630 [2700]	49.0	33.0	22	22	27	M 22x1.5	10x2	11.0
DS-RSDKO 14/12	14	12	S 630 [2700]	49.0	33.0	22	24	27	M 22x1.5	10x2	11.9
DS-RSDKO 16/6	16	6	S 630 [2700]	46.5	32.0	22	17	30	M 24x1.5	12x2	12.7
DS-RSDKO 16/8	16	8	S 630 [2700]	46.5	32.0	22	19	30	M 24x1.5	12x2	14.8
DS-RSDKO 16/10	16	10	S 630 [2700]	47.5	31.5	22	22	30	M 24x1.5	12x2	14.8
DS-RSDKO 16/12	16	12	S 630 [2700]	47.5	31.5	22	24	30	M 24x1.5	12x2	15.5
DS-RSDKO 16/14	16	14	S 630 [2700]	50.5	33.0	24	27	30	M 24x1.5	12x2	16.3
DS-RSDKO 20/6	20	6	S 400 [1700]	50.5	36.0	27	17	36	M 30x2	16.3x2.4	18.9
DS-RSDKO 20/8	20	8	S 400 [1700]	50.5	36.0	27	19	36	M 30x2	16.3x2.4	20.5
DS-RSDKO 20/10	20	10	S 400 [1700]	51.5	35.5	27	22	36	M 30x2	16.3x2.4	20.6
DS-RSDKO 20/12	20	12	S 400 [1700]	51.5	35.5	27	24	36	M 30x2	16.3x2.4	21.3
DS-RSDKO 20/14	20	14	S 400 [1700]	54.5	37.0	27	27	36	M 30x2	16.3x2.4	23.2
DS-RSDKO 20/16	20	16	S 400 [1700]	54.5	36.5	27	30	36	M 30x2	16.3x2.4	25.9
DS-RSDKO 25/6	25	6	S 400 [1700]	53.0	38.5	36	17	46	M 36x2	20.3x2.4	30.8
DS-RSDKO 25/8	25	8	S 400 [1700]	53.0	38.5	36	19	46	M 36x2	20.3x2.4	31.9
DS-RSDKO 25/10	25	10	S 400 [1700]	54.0	38.0	36	22	46	M 36x2	20.3x2.4	33.2
DS-RSDKO 25/12	25	12	S 400 [1700]	54.0	38.0	36	24	46	M 36x2	20.3x2.4	33.4
DS-RSDKO 25/14	25	14	S 400 [1700]	57.0	39.5	36	27	46	M 36x2	20.3x2.4	35.1
DS-RSDKO 25/16	25	16	S 400 [1700]	57.0	39.0	36	30	46	M 36x2	20.3x2.4	37.3
DS-RSDKO 25/20	25	20	S 400 [1700]	60.5	39.0	36	36	46	M 36x2	20.3x2.4	43.6
DS-RSDKO 30/6	30	6	S 400 [1700]	58.5	44.0	41	17	50	M 42x2	25.3x2.4	42.9
DS-RSDKO 30/8	30	8	S 400 [1700]	58.5	44.0	41	19	50	M 42x2	25.3x2.4	43.1
DS-RSDKO 30/10	30	10	S 400 [1700]	59.5	43.5	41	22	50	M 42x2	25.3x2.4	43.6
DS-RSDKO 30/12	30	12	S 400 [1700]	59.5	43.5	41	24	50	M 42x2	25.3x2.4	44.3
DS-RSDKO 30/14	30	14	S 400 [1700]	62.5	45.0	41	27	50	M 42x2	25.3x2.4	46.1
DS-RSDKO 30/16	30	16	S 400 [1700]	62.5	44.5	41	30	50	M 42x2	25.3x2.4	48.7
DS-RSDKO 30/20	30	20	S 400 [1700]	66.0	44.5	41	36	50	M 42x2	25.3x2.4	53.6
DS-RSDKO 30/25	30	25	S 400 [1700]	69.0	45.0	41	46	50	M 42x2	25.3x2.4	67.3
DS-RSDKO 38/6	38	6	S 400 [1700]	62.0	47.5	50	17	60	M 52x2	33.3x2.4	70.8
DS-RSDKO 38/8	38	8	S 400 [1700]	62.0	47.5	50	19	60	M 52x2	33.3x2.4	71.0
DS-RSDKO 38/10	38	10	S 400 [1700]	63.0	47.0	50	22	60	M 52x2	33.3x2.4	71.4
DS-RSDKO 38/12	38	12	S 400 [1700]	63.0	47.0	50	24	60	M 52x2	33.3x2.4	72.0
DS-RSDKO 38/14	38	14	S 400 [1700]	66.0	48.5	50	27	60	M 52x2	33.3x2.4	74.3
DS-RSDKO 38/16	38	16	S 400 [1700]	66.0	48.0	50	30	60	M 52x2	33.3x2.4	77.0
DS-RSDKO 38/20	38	20	S 400 [1700]	69.5	48.0	50	36	60	M 52x2	33.3x2.4	81.2
DS-RSDKO 38/25	38	25	S 400 [1700]	72.5	48.5	50	46	60	M 52x2	33.3x2.4	85.0
DS-RSDKO 38/30	38	30	S 400 [1700]	75.5	49.0	50	50	60	M 52x2	33.3x2.4	87.8

L = approximate length, with nut tightened

Please see "Engineering and technical data - Selecting the correct tube fitting" for
- reducing example.

- more information on pressure.