


COUPLINGS

STRAIGHT COUPLING AND REDUCER

EDKO STRAIGHT COUPLING TAPER

Taper on both ends and O-ring to DIN 3865.

O-ring NBR (e.g. Perbunan), according to FPM (e.g. Viton) upon request.



description	pipe OD	PN series	L ₁	L ₂	S ₁	O-Ring
EDKO 6-L	6	L 500 (2200)	33.0	36.0	17	4x1.5
EDKO 8-L	8	L 500 (2200)	33.0	36.0	17	6x1.5
EDKO 10-L	10	L 500 (2200)	35.0	37.0	19	7.5x1.5
EDKO 12-L	12	L 400 (1700)	35.0	37.0	22	9x1.5
EDKO 15-L	15	L 400 (1700)	38.0	40.0	27	12x2
EDKO 18-L	18	L 400 (1700)	39.5	42.5	32	15x2
EDKO 22-L	22	L 250 (1100)	44.0	47.0	36	20x2
EDKO 28-L	28	L 250 (1100)	46.0	49.0	41	26x2
EDKO 35-L	35	L 250 (1100)	52.0	58.0	50	32x2.5
EDKO 42-L	42	L 250 (1100)	52.0	59.0	60	38x2.5
EDKO 6-S	6	S 800 (3400)	36.0	39.0	17	4x1.5
EDKO 8-S	8	S 800 (3400)	36.0	39.0	19	6x1.5
EDKO 10-S	10	S 800 (3400)	40.0	43.0	22	7.5x1.5
EDKO 12-S	12	S 630 (2700)	41.0	44.0	24	9x1.5
EDKO 14-S	14	S 630 (2700)	44.0	48.0	27	10x2
EDKO 16-S	16	S 630 (2700)	45.0	50.0	30	12x2
EDKO 20-S	20	S 400 (1700)	54.0	60.0	36	16.3x2.4
EDKO 25-S	25	S 400 (1700)	59.0	66.0	46	20.3x2.4
EDKO 30-S	30	S 400 (1700)	63.0	73.0	50	25.3x2.4
EDKO 38-S	38	S 400 (1700)	68.0	83.0	60	33.3x2.4

Please see "Engineering and technical data - Selecting the correct tube fitting" for more information on pressure.