


COUPLINGS

ADJUSTABLE COUPLING

VBDKO ADJUSTABLE MALE STUD ELBOW

With taper and O-ring according to DIN 3865.

O-ring NBR (e.g. Perbunan), FPM (e.g. Viton) upon request.



description	pipe OD	PN series	L ₂	L	I	S	S ₁	S ₃	kg % pc	O-Ring
DS-VBDKO 6-L	6	L 500 (2200)	26.0	27	12.0	12	17	14	4.0	4x1.5
DS-VBDKO 8-L	8	L 500 (2200)	27.5	29	14.0	12	17	17	5.5	6x1.5
DS-VBDKO 10-L	10	L 500 (2200)	29.0	30	15.0	14	19	19	7.1	7.5x1.5
DS-VBDKO 12-L	12	L 400 (1700)	29.5	32	17.0	17	22	22	9.6	9x1.5
DS-VBDKO 15-L	15	L 400 (1700)	32.5	36	21.0	19	27	27	16.6	12x2
DS-VBDKO 18-L	18	L 400 (1700)	35.5	40	23.5	24	32	32	23.6	15x2
DS-VBDKO 22-L	22	L 250 (1100)	38.5	44	27.5	27	36	36	32.7	20x2
DS-VBDKO 28-L	28	L 250 (1100)	41.5	47	30.5	36	41	41	52.4	26x2
DS-VBDKO 35-L	35	L 250 (1100)	51.0	56	34.5	41	50	50	68.8	32x2.5
DS-VBDKO 42-L	42	L 250 (1100)	56.0	63	40.0	50	60	60	108.0	38x2.5
DS-VBDKO 6-S	6	S 800 (3400)	27.0	31	16.0	14	17	17	6.2	4x1.5
DS-VBDKO 8-S	8	S 800 (3400)	27.5	32	17.0	17	19	19	7.4	6x1.5
DS-VBDKO 10-S	10	S 800 (3400)	30.0	34	17.5	19	22	22	11.3	7.5x1.5
DS-VBDKO 12-S	12	S 630 (2700)	31.0	38	21.5	22	24	24	14.0	9x1.5
DS-VBDKO 14-S	14	S 630 (2700)	35.0	40	22.0	19	27	27	19.3	10x2
DS-VBDKO 16-S	16	S 630 (2700)	36.5	43	24.5	24	30	30	25.8	12x2
DS-VBDKO 20-S	20	S 400 (1700)	44.5	48	26.5	27	36	36	40.3	16.3x2.4
DS-VBDKO 25-S	25	S 400 (1700)	50.0	54	30.0	36	46	46	75.1	20.3x2.4
DS-VBDKO 30-S	30	S 400 (1700)	55.0	62	35.5	41	50	50	96.4	25.3x2.4
DS-VBDKO 38-S	38	S 400 (1700)	63.0	72	41.0	50	60	60	142.5	33.3x2.4

L = approximate length with nut tightened

Please see "Engineering and technical data - Selecting the correct tube fitting" for more information on pressure.