

PIPE CONNECTIONS REDUCING ADAPTORS


THE WORLD OF TUBE FITTINGS

RI REDUCING ADAPTOR

BSP parallel.

Stud face form B.

Other sizes and threads upon request.



| description G1-G2 | PB | l | i | S | d ₃ | t ₁ | kg % pc |
|-------------------|-----|------|----|----|----------------|----------------|------------|
| RI 3/8" - 1/8" | 630 | 22.5 | 12 | 22 | 22 | 8.0 | 4.0 |
| RI 1/2-1/4 | 400 | 24.0 | 14 | 27 | 26 | 8.0 | 6.0 |
| RI 1/2-1/8 | 400 | 24.0 | 14 | 27 | 26 | 12.0 | 6.0 |
| RI 3/4-1/4 | 400 | 26.0 | 16 | 32 | 32 | 12.0 | 9.5 |
| RI 3/4-3/8 | 400 | 26.0 | 16 | 32 | 32 | 12.0 | 9.0 |
| RI 1-1/4 | 400 | 29.0 | 18 | 41 | 39 | 12.0 | 20.0 |
| RI 1-3/8 | 400 | 29.0 | 18 | 41 | 39 | 12.0 | 18.0 |
| RI 1-1/2 | 400 | 29.0 | 18 | 41 | 39 | 14.0 | 16.0 |
| RI 1 1/4-1/2 | 250 | 32.0 | 20 | 50 | 49 | 14.0 | 31.0 |
| RI 1 1/4-3/4 | 250 | 32.0 | 20 | 50 | 49 | 16.0 | 27.0 |
| RI 1 1/2-1/2 | 250 | 36.0 | 22 | 55 | 55 | 14.0 | 47.0 |
| RI 1 1/2-3/4 | 250 | 36.0 | 22 | 55 | 55 | 16.0 | 43.0 |
| RI 1 1/2-1 | 250 | 36.0 | 22 | 55 | 55 | 18.0 | 34.5 |
| RI 1/8-1/4 | 630 | 31.0 | 8 | 19 | 14 | 17.0 | 3.6 |
| RI 1/8-3/8 | 630 | 32.0 | 8 | 24 | 14 | 17.0 | 4.5 |
| RI 1/4-1/8 | 630 | 28.0 | 12 | 19 | 18 | 12.0 | 3.6 |
| RI 1/4-3/8 | 630 | 36.0 | 12 | 24 | 18 | 17.0 | 6.6 |
| RI 1/4-1/2 | 630 | 40.0 | 12 | 30 | 18 | 20.0 | 8.5 |
| RI 1/4-3/4 | 400 | 43.0 | 12 | 36 | 18 | 22.0 | 17.3 |
| RI 3/8-1/4 | 630 | 36.0 | 12 | 22 | 22 | 17.0 | 3.0 |
| RI 3/8-1/2 | 630 | 41.0 | 12 | 30 | 22 | 20.0 | 9.0 |
| RI 3/8-3/4 | 400 | 44.0 | 12 | 36 | 22 | 22.0 | 17.5 |
| RI 1/2-3/8 | 400 | 36.0 | 14 | 27 | 26 | 17.0 | 9.5 |
| RI 1/2-3/4 | 400 | 46.0 | 14 | 36 | 26 | 22.0 | 18.0 |
| RI 1/2-1 | 400 | 49.0 | 14 | 41 | 26 | 24.5 | 22.5 |
| RI 1/2-1 1/4 | 250 | 53.0 | 14 | 55 | 26 | 26.5 | 47.0 |
| RI 3/4-1/2 | 400 | 41.0 | 16 | 32 | 32 | 20.0 | 15.0 |
| RI 3/4-1 | 400 | 51.0 | 16 | 41 | 32 | 24.5 | 23.5 |
| RI 3/4-1 1/4 | 250 | 55.0 | 16 | 55 | 32 | 26.5 | 48.3 |
| RI 3/4-1 1/2 | 250 | 57.0 | 16 | 60 | 32 | 28.5 | 54.5 |
| RI 1-3/4 | 400 | 47.0 | 18 | 41 | 39 | 22.0 | 28.0 |
| RI 1-1 1/4 | 250 | 57.0 | 18 | 55 | 39 | 26.5 | 51.0 |
| RI 1-1 1/2 | 250 | 59.0 | 18 | 60 | 39 | 28.5 | 56.5 |
| RI 1 1/4-1 | 250 | 52.0 | 20 | 50 | 49 | 24.5 | 45.5 |
| RI 1 1/4-1 1/2 | 250 | 60.0 | 20 | 60 | 49 | 28.5 | 58.0 |
| RI 1 1/2-1 1/4 | 250 | 58.0 | 22 | 55 | 55 | 26.5 | 53.0 |

Please see "Engineering and technical data - Selecting the correct tube fitting" for
- reducing example.
- more information on pressure.