

**711**

**Hydraulic Hose - No-Skive  
Meets SAE 100R11 Pressure**



# Part Number	Hose I.D.		Hose O.D.		Working Pressure		Burst Pressure		Minimum Bend Radius		Weight		Parkrimp Fitting		Field Attachable Fitting	
	inch	mm	inch	mm	psi	MPa	psi	MPa	inch	mm	lbs/ft	kg/m	Series	Page	Series	Page
711-24	1-1/2	38,0	2.07	52,8	3000	21,0	12000	84,0	22	560	2.01	2,99	71	B-81		
711-32	2	51,0	2.59	65,9	3000	21,0	12000	84,0	28	710	2.75	4,09	71	B-81		

**Construction:** Synthetic rubber tube; four spirals of high tensile steel wire reinforcement; MSHA accepted gray synthetic rubber cover.

**Application and Temperature Range:**

High pressure hose for use with: Petroleum based hydraulic fluids and lubricating oils within a temperature range of -40°F to +212°F (-40°C to 100°C); Water, water/oil emulsion, and water/glycol hydraulic fluids up to +185°F (+85°F); Air within a temperature range of -40°F to +158°F (-40°C to +70°C). For air above 250 psi (1,7 MPa) the cover should be pin-pricked

**Fittings:** Parkrimp fittings 71 Series. See Section C for assembly instructions.

**Hose cover does not have to be removed to attach Parker No-Skive fittings.**