



Air and Multi-Purpose Hose

Adapta Flex™ Red

(Specification 3204E, 3204S)

Standard Reel Packaging

Nom. I.D.	⌀	Nom. O.D.	⌀	Max. W.P.	⌚	Suction	⌀	Min. Bend Radius	⌚	Wt. Per Ft.	⌚	Standard Pack	Stock (X) or Minimum Order Qty.	Gates Item No.	
(In.)	(mm)	(In.)	(mm)	(psi)	(MPa)	(In. Hg)	(mm Hg)	(In.)	(mm)	(Lbs.)	(Kg)				
1/4	6.4	.50	12.7	200	1.38	30.0	762	3.0	76	.09	.04	Reel	X	3204-1301	
1/4	6.4	.50	12.7	250	1.72	30.0	762	3.0	76	.08	.04	Reel	X	3204-1304	
1/4	6.4	.53	13.5	300	2.07	30.0	762	3.0	76	.10	.05	Reel	X	3204-1307	
1/4	6.4	.62	15.8	250	1.72	30.0	762	3.0	76	.08	.04	Reel	25,000 ft.	3204-1386	
5/16	7.9	.53	13.5	200	1.38	30.0	762	3.0	76	.09	.04	Reel	X	3204-1316	
3/8	9.5	.66	16.8	200	1.38	30.0	762	3.0	76	.14	.06	Reel	X	3204-1319	
3/8	9.5	.66	16.8	250	1.72	30.0	762	3.0	76	.14	.06	Reel	X	3204-1322	
3/8	9.5	.67	17.0	300	2.07	30.0	762	3.0	76	.15	.07	Reel	X	3204-1325	
1/2	12.7	.81	20.6	200	1.38	25.0	635	5.0	127	.20	.09	Reel	X	3204-1328	
1/2	12.7	.81	20.6	250	1.72	25.0	635	5.0	127	.19	.09	Reel	X	3204-1331	
1/2	12.7	.83	21.1	300	2.07	25.0	635	5.0	127	.20	.09	Reel	X	3204-1334	
5/8	15.9	.97	24.6	200	1.38	20.0	508	6.0	152	.26	.12	Reel	X	3204-1337	
5/8	15.9	.97	24.6	250	1.72	20.0	508	6.0	152	.26	.12	Reel	X	3204-1340	
5/8	15.9	.97	24.6	250	1.72	20.0	508	6.0	152	.26	.12	50 ft.	25,000 ft.	3204-5415	
3/4	19.1	1.11	28.2	200	1.38	15.0	381	6.0	152	.31	.16	Reel	X	3204-1346	
3/4	19.1	1.11	29.2	250	1.72	20.0	508	6.0	152	.35	.16	Reel	X	3204-1349	
3/4	19.1	1.15	29.2	300	2.07	15.0	381	6.0	152	.35	.16	Reel	X	3204-1355	
3/4	19.1	1.15	29.2	250	1.72	20.0	508	6.0	152	.35	.16	50 ft.	200 ft. (X)	3204-5420	
3/4	19.1	1.15	29.2	300	2.07	15.0	381	6.0	152	.35	.16	50 ft.	200 ft. (X)	3204-5675	
1	25.4	1.39	35.3	150	1.03	10.0	254	8.0	203	.48	.22	Reel	X	3204-1358	
1	25.4	1.39	35.3	200	1.38	10.0	254	8.0	203	.48	.22	Reel	X	3204-1361	
1	25.4	1.47	37.3	300	2.07	10.0	254	8.0	203	.54	.25	Reel	X	3204-1364	

NOTE: For 1 1/4" and 1 1/2" I.D. see Duro Flex®.

Adapta Flex™ Assemblies

Nom. I.D.	⌀	Nom. O.D.	⌀	Max. W.P.	⌚	Suction	⌀	Min. Bend Radius	⌚	Wt. Per Ea.	⌚	Standard Pack	Stock (X) or Minimum Order Qty.	Gates Item No.	
(In.)	(mm)	(In.)	(mm)	(psi)	(MPa)	(In. Hg)	(mm Hg)	(In.)	(mm)	(Lbs.)	(Kg)				
3/8	9.5	.66	16.8	250	1.72	30.0	762	3.0	76	7.72	3.51	50 ft.	8 ea. (X)	3204-1720	
3/8	9.5	.66	16.8	250	1.72	30.0	762	3.0	76	6.53	2.97	50 ft.-BP**	54 ea. (X)	3204-1900	

NOTE: **BP - Bulk Pack, 54 assemblies per pallet carton.

RECOMMENDED FOR: Air and water applications requiring maximum flexibility in any industry, including mining, construction, agriculture, vehicle repair and in-plant operations. Outstanding resistance to heat and ozone. Suitable for light agricultural spraying, such as dilute solutions of herbicides.

TEMPERATURE: -40°F to +200°F (-40°C to +93°C) continuous service.

CONSTRUCTION: **Tube:** Type P (EPDM). Black.
Reinforcement: Synthetic, high tensile textile cord.
Cover: Type P (EPDM). Red. All sizes through 1/2" are perforated.
Design Factor: 3:1

COUPLINGS: 19 (up through 1/2" only), 1, 3 or 4, (up through 1/2" with 20 brass ferrules, up through 1" with bands), 72 Gates Power Crimp® or 75 Gates GLX®. Reference the Hose Coupling Section.

PACKAGING: Exact length reels: 500' in one continuous length.
Minimum of 90% of hose reels will be 1-piece lengths.
1/4" through 3/4": Packaged in 500' to 700' reels. Maximum 2 pieces in 50' increments.
3/8" x 50' coupled assemblies: **BP - Bulk Pack, 54 assemblies per pallet carton.
3/8" x 50' coupled assemblies: Coiled in a carton, 5 assemblies per carton.
5/8" x 50': Packaged 250' per carton, each length coiled and tied.
3/4" x 50': Packaged 200' per carton, each length coiled and tied.
1": Packaged in 300' to 400' reels. Maximum 2 pieces in 50' increments.

BRANDING: Continuous ink brand. Example: "GATES® ADAPTA FLEX™ MULTI-PURPOSE 3/8 INCH (9.5mm) 250 PSI (1.72MPa) WP MADE IN USA"

SPECIAL ORDER REQUIREMENTS: Special production runs require minimum order quantities of 25,000 feet per size.

REMNANT LENGTHS: None.

STANDARDS: **Tube:** ARPM (Class C) Limited oil resistance.

ACID-
CHEMICAL

AIR AND
MULTI-
PURPOSE

FOOD AND
BEVERAGE

MARINE

MATERIAL
HANDLING

MINING

OILFIELD

PETROLEUM
TRANSFER

PRESSURE
WASHER

STEAM

WATER

CLAMPS

COUPLINGS
AND
FERRULES

HOSE FINDER

CHEMICAL
RESISTANCE
TABLE



Powering Progress.

gates.com/industrialhose

ACID-
CHEMICALAIR AND
MULTI-
PURPOSEFOOD AND
BEVERAGE

MARINE

MATERIAL
HANDLING

MINING

OILFIELD

PETROLEUM
TRANSFERPRESSURE
WASHER

STEAM

WATER

CLAMPS

COUPLINGS
AND
FERRULESHOSE
FINDERCHEMICAL
RESISTANCE
TABLE

Air and Multi-Purpose Hose

Adapta Flex™ Red
1 Piece Reel

(Specification 3204E, 3204S)

Exact Length 500 Foot One Piece Reels

Nom. I.D.	Ø	Nom. O.D.	Ø	Max. W.P.	⚡	Suction	Ø	Min. Bend Radius	R ₂	Wt. Per Ft.	⚖	Standard Pack	Stock (X) or Minimum Order Qty.	Gates Item No.	
(In.)	(mm)	(In.)	(mm)	(psi)	(MPa)	(In. Hg)	(mm Hg)	(In.)	(mm)	(Lbs.)	(Kg)				
1/4	6.4	.50	12.7	200	1.38	30.0	762	3.0	76	.09	.04	Reel	500 ft.	3204-5301	
1/4	6.4	.50	12.7	250	1.72	30.0	762	3.0	76	.08	.04	Reel	500 ft.	3204-5304	
1/4	6.4	.53	13.5	300	2.07	30.0	762	3.0	76	.10	.05	Reel	500 ft.	3204-5307	
3/8	9.5	.66	16.8	200	1.38	30.0	762	3.0	76	.14	.06	Reel	500 ft.	3204-5319	
3/8	9.5	.66	16.8	250	1.72	30.0	762	3.0	76	.14	.06	Reel	500 ft.	3204-5321	
3/8	9.5	.67	17.0	300	2.07	30.0	762	3.0	76	.15	.07	Reel	500 ft.	3204-5326	
1/2	12.7	.81	20.6	200	1.38	25.0	635	5.0	127	.20	.09	Reel	500 ft.	3204-5328	
1/2	12.7	.81	20.6	250	1.72	25.0	635	5.0	127	.19	.09	Reel	500 ft.	3204-5333	
1/2	12.7	.83	21.1	300	2.07	25.0	635	5.0	127	.20	.09	Reel	500 ft.	3204-5334	
5/8	15.9	.97	24.6	200	1.38	20.0	508	6.0	152	.26	.12	Reel	500 ft.	3204-5337	
5/8	15.9	.97	24.6	250	1.72	20.0	508	6.0	152	.26	.12	Reel	500 ft.	3204-5341	
3/4	19.1	1.11	28.2	200	1.38	15.0	381	6.0	152	.31	.14	Reel	500 ft.	3204-5346	
3/4	19.1	1.11	29.2	250	1.72	20.0	508	6.0	152	.35	.16	Reel	500 ft.	3204-5349	
3/4	19.1	1.15	29.2	300	2.07	15.0	381	6.0	152	.35	.16	Reel	500 ft.	3204-5355	

RECOMMENDED FOR: Air and water applications requiring maximum flexibility in any industry, including mining, construction, agriculture, vehicle repair and in-plant operations. Outstanding resistance to heat and ozone. Suitable for light agricultural spraying, such as dilute solutions of herbicides.

TEMPERATURE: -40°F to +200°F (-40°C to +93°C) continuous service.

CONSTRUCTION: **Tube:** Type P (EPDM). Black.
Reinforcement: Synthetic, high tensile textile cord.
Cover: Type P (EPDM). Red. All sizes through 1/2" are perforated.
Design Factor: 3:1

COUPLINGS: 19 (up through 1/2" only), 1, 3 or 4, (up through 1/2" with 20 brass ferrules, up through 1" with bands), 72 Gates Power Crimp® or 75 Gates GLX®. Reference the Hose Coupling Section.

PACKAGING: Exact length reels: 500' in one continuous length.
 Minimum of 90% of hose reels will be 1-piece lengths.
 1/4" through 3/4": Packaged in 500' to 700' reels. Maximum 2 pieces in 50' increments.
 3/8" x 50' coupled assemblies: **BP - Bulk Pack, 54 assemblies per pallet carton.
 3/8" x 50' coupled assemblies: Coiled in a carton, 5 assemblies per carton.
 5/8" x 50': Packaged 250' per carton, each length coiled and tied.
 3/4" x 50': Packaged 200' per carton, each length coiled and tied.
 1": Packaged in 300' to 400' reels. Maximum 2 pieces in 50' increments.

BRANDING: Continuous ink brand. Example: "GATES® ADAPTA FLEX™ MULTI-PURPOSE 3/8 INCH (9.5mm) 250 PSI (1.72MPa) WP MADE IN USA"

SPECIAL ORDER REQUIREMENTS: Special production runs require minimum order quantities of 25,000 feet per size.

REMNANT LENGTHS: None.

STANDARDS: **Tube:** ARPM (Class C) Limited oil resistance.





Air and Multi-Purpose Hose

Adapta Flex™ - UPS Shippable Reels

(Specification 3204E, 3204EB, 3204SB)

Red Cover (3204E)

Nom. I.D.	⊖	Nom. O.D.	⊖	Max. W.P.	⊖	Suction	⊖	Min. Bend Radius	⊖	Wt. Per Ft.	⊖	Standard Pack	Stock (X) or Minimum Order Qty.	Gates Item No.
(In.)	(mm)	(In.)	(mm)	(psi)	(MPa)	(In. Hg)	(mm Hg)	(In.)	(mm)	(Lbs.)	(Kg)			
1/4	6.4	.50	12.7	200	1.38	30.0	762	3.0	76	.09	.04	Reel	X	3204-1373
3/8	9.5	.66	16.8	200	1.38	30.0	762	3.0	76	.14	.06	Reel	X	3204-1375
1/2	12.7	.81	20.6	200	1.38	25.0	635	5.0	127	.23	.10	Reel	X	3204-1377
5/8	15.9	.97	24.6	200	1.38	20.0	508	6.0	152	.26	.12	Reel	X	3204-1379
3/4	19.1	1.11	28.2	200	1.38	15.0	381	6.0	152	.31	.14	Reel	X	3204-1381
1	25.4	1.40	35.6	200	1.38	10.0	254	8.0	203	.45	.20	Reel	X	3204-1383

Black Cover (3204EB, 3204SB)

Nom. I.D.	⊖	Nom. O.D.	⊖	Max. W.P.	⊖	Suction	⊖	Min. Bend Radius	⊖	Wt. Per Ft.	⊖	Standard Pack	Stock (X) or Minimum Order Qty.	Gates Item No.
(In.)	(mm)	(In.)	(mm)	(psi)	(MPa)	(In. Hg)	(mm Hg)	(In.)	(mm)	(Lbs.)	(Kg)			
1/4	6.4	.50	12.7	200	1.38	30.0	762	3.0	76	.09	.04	Reel	X	3204-1408
1/2	12.7	.81	20.6	200	1.38	25.0	635	5.0	127	.20	.09	Reel	X	3204-1414
3/4	19.1	1.15	29.2	250	1.72	20.0	508	6.0	152	.35	.16	Reel	X	3204-1427
1	25.4	1.40	35.6	200	1.38	10.0	254	8.0	203	.48	.22	Reel	X	3204-1432

RECOMMENDED FOR: Air and water applications requiring maximum flexibility in any industry, including mining, construction, agriculture, vehicle repair and in-plant operations. Outstanding resistance to heat and ozone. Suitable for light agricultural spraying, such as dilute solutions of herbicides.

TEMPERATURE: -40°F to +200°F (-40°C to +93°C) continuous service.

CONSTRUCTION: **Tube:** Type P (EPDM). Black.
Reinforcement: Synthetic, high tensile textile cord.
Cover: Type P (EPDM). Red or Black. All sizes through 1/2" are perforated. (Blue, green and yellow covers available on special order).
Design Factor: 3:1

COUPLINGS: 19 (up through 1/2" only), 1, 3 or 4, (up through 1/2" with 20 brass ferrules, up through 1" with bands), 72 Gates Power Crimp® or 75 Gates GLX®. Reference the Hose Coupling Section.

PACKAGING: All sizes packaged on single piece reels meet UPS (United Parcel Service) size and weight requirements.
1/4" and 3/8": Packaged in 375' to 425' single piece reels.
1/2": Packaged in 225' to 275' single piece reels.
5/8": Packaged in 235' to 265' single piece reels.
3/4": Packaged in 185' to 215' single piece reels.
1": Packaged in 100' to 125' single piece reels.

BRANDING: Continuous ink brand. Example: "GATES® ADAPTA FLEX™ MULTI-PURPOSE 3/8 INCH (9.5mm) 200 PSI (1.38MPa) WP MADE IN USA"

SPECIAL ORDER REQUIREMENTS: Special production runs require minimum order quantities of 25,000 feet per size. Black, blue, green and yellow covers are made to order and require 25,000 feet orders by size/color. Prices for colors as follows from list price: Black less 5% (x.95). Blue, green and yellow contact Gates Corporation for pricing, order requirements and availability.

REMNAINT LENGTHS: None.

STANDARDS: Reels meet size and weight requirements of UPS (United Parcel Service).
Tube: ARPM (Class C) Limited oil resistance.

ACID-
CHEMICAL

AIR AND
MULTI-
PURPOSE

FOOD AND
BEVERAGE

MARINE

MATERIAL
HANDLING

MINING

OILFIELD

PETROLEUM
TRANSFER

PRESSURE
WASHER

STEAM

WATER

CLAMPS

COUPLINGS
AND
FERRULES

HOSE FINDER

CHEMICAL
RESISTANCE
TABLE



Powering Progress.

gates.com/industrialhose

ACID-
CHEMICALAIR AND
MULTI-
PURPOSEFOOD AND
BEVERAGE

MARINE

MATERIAL
HANDLING

MINING

OILFIELD

PETROLEUM
TRANSFERPRESSURE
WASHER

STEAM

WATER

CLAMPS

COUPLINGS
AND
FERRULESHOSE
FINDERCHEMICAL
RESISTANCE
TABLE

Air and Multi-Purpose Hose

Adapta Flex™ Black
(Specification 3204EB, 3204SB)

Standard Reel Packaging

Nom. I.D.	⊖	Nom. O.D.	⊖	Max. W.P.	⌚	Suction	⊖	Min. Bend Radius	⌚	Wt. Per Ft.	⌚	Standard Pack	Stock (X) or Minimum Order Qty.	Gates Item No.
(In.)	(mm)	(In.)	(mm)	(psi)	(MPa)	(In. Hg)	(mm Hg)	(In.)	(mm)	(Lbs.)	(Kg)			
1/4	6.4	.50	12.7	200	1.38	30.0	762	3.0	76	.09	.04	Reel	X	3204-1401
1/4	6.4	.50	12.7	250	1.72	30.0	762	3.0	76	.08	.04	Reel	25,000 ft.	3204-1404
1/4	6.4	.62	15.8	250	1.72	30.0	762	3.0	76	.08	.04	Reel	25,000 ft.	3204-1406
3/8	9.5	.66	16.8	200	1.38	30.0	762	3.0	76	.14	.06	Reel	X	3204-1407
3/8	9.5	.66	16.8	250	1.72	30.0	762	3.0	76	.14	.06	Reel	X	3204-1410
1/2	12.7	.81	20.6	200	1.38	25.0	635	5.0	127	.20	.09	Reel	X	3204-1413
1/2	12.7	.81	20.6	250	1.72	25.0	635	5.0	127	.19	.09	Reel	X	3204-1416
5/8	15.9	.97	24.6	200	1.38	20.0	508	6.0	152	.26	.12	Reel	X	3204-1419
3/4	19.1	1.11	28.2	200	1.38	15.0	381	6.0	152	.31	.14	Reel	X	3204-1422
3/4	19.1	1.15	29.2	250	1.72	20.0	508	6.0	152	.35	.16	Reel	X	3204-1425
3/4	19.1	1.15	29.2	250	1.72	20.0	508	6.0	152	.35	.16	50 ft.	200 ft. (X)	3204-5820
1	25.4	1.40	35.6	150	1.03	10.0	254	8.0	203	.48	.22	Reel	X	3204-1428
1	25.4	1.40	35.6	200	1.38	10.0	254	8.0	203	.48	.22	Reel	X	3204-1431
1 1/4	31.8	1.73	43.9	250	1.72	10.0	254	10.0	254	.68	.31	Reel	X	3204-1434
1 1/2	38.1	1.98	50.3	250	1.72	10.0	254	12.0	305	.85	.39	Reel	X	3204-1437

Exact Length 500 Foot One Piece Reels

Nom. I.D.	⊖	Nom. O.D.	⊖	Max. W.P.	⌚	Suction	⊖	Min. Bend Radius	⌚	Wt. Per Ft.	⌚	Standard Pack	Stock (X) or Minimum Order Qty.	Gates Item No.
(In.)	(mm)	(In.)	(mm)	(psi)	(MPa)	(In. Hg)	(mm Hg)	(In.)	(mm)	(Lbs.)	(Kg)			
1/4	6.4	.50	12.7	200	1.38	30.0	762	3.0	76	.09	.04	Reel	500 ft.	3204-4402
3/8	9.5	.66	16.8	200	1.38	30.0	762	3.0	76	.14	.06	Reel	500 ft.	3204-4407
3/8	9.5	.66	16.8	250	1.72	30.0	762	3.0	76	.14	.06	Reel	500 ft.	3204-4431
1/2	12.7	.81	20.6	200	1.38	25.0	635	5.0	127	.20	.09	Reel	500 ft.	3204-4413
1/2	12.7	.81	20.6	250	1.72	25.0	635	5.0	127	.19	.09	Reel	500 ft.	3204-4432
3/4	19.1	1.11	28.2	200	1.38	15.0	381	6.0	152	.31	.14	Reel	500 ft.	3204-4422
3/4	19.1	1.15	29.2	250	1.72	20.0	508	6.0	152	.35	.16	Reel	500 ft.	3204-4433

Adapta Flex™ Black Cover Assemblies

Nom. I.D.	⊖	Nom. O.D.	⊖	Max. W.P.	⌚	Suction	⊖	Min. Bend Radius	⌚	Wt. Per Ea.	⌚	Standard Pack	Stock (X) or Minimum Order Qty.	Gates Item No.
(In.)	(mm)	(In.)	(mm)	(psi)	(MPa)	(In. Hg)	(mm Hg)	(In.)	(mm)	(Lbs.)	(Kg)			
3/8	9.5	.66	16.8	250	1.72	30.0	762	3.0	76	7.43	3.38	50 ft.	8 ea. (X)	3204-1721

RECOMMENDED FOR: Air and water applications requiring maximum flexibility in any industry, including mining, construction, agriculture, vehicle repair and in-plant operations. Outstanding resistance to heat and ozone. Suitable for light agricultural spraying, such as dilute solutions of herbicides.

TEMPERATURE: -40°F to +200°F (-40°C to +93°C) continuous service.

CONSTRUCTION: **Tube:** Type P (EPDM). Black.

Reinforcement: Synthetic, high tensile textile cord.

Cover: Type P (EPDM). Black. All sizes through 1/2" are perforated.

Design Factor: 3:1

COUPLINGS: 19 (up through 1/2" only), 1, 3 or 4, (up through 1/2" with 20 brass ferrules, up through 1" with bands), 72 Gates Power Crimp® or 75 Gates GLX®. Reference the Hose Coupling Section.

PACKAGING: Exact length reels: 500' in one continuous length.

Minimum of 90% of hose reels will be 1-piece lengths.

1/4" through 3/4": Packaged in 500' to 700' reels. Maximum 2 pieces in 50' increments.

3/8" x 50' coupled assemblies: Coiled in a carton, 5 assemblies per carton.

3/4" x 50': Packaged 200' per carton, each length coiled and tied.

1": Packaged in 300' to 400' reels. Maximum 2 pieces in 50' increments.

1 1/4": Packaged in 300' reels. Maximum 2 pieces in 50' increments.

1 1/2": Packaged in 250' reels. Maximum 2 pieces in 50' increments.

BRANDING: Continuous ink brand. Example: "GATES® ADAPTA FLEX™ MULTI-PURPOSE 3/8 INCH (9.5mm) 250 PSI (1.72MPa) WP MADE IN USA"

SPECIAL ORDER REQUIREMENTS:

Special production runs require minimum order quantities of 25,000 feet per size.

REMANENT LENGTHS:

None.

STANDARDS:

Tube: ARPM (Class C) Limited oil resistance.

Cover: ARPM (Class C) Limited oil resistance.





Air and Multi-Purpose Hose

Adapta Flex™ Blue, Green & Yellow Cover

(Specification 3204BL, GR, YL)

	Nom. I.D.	⊖	Nom. O.D.	⊕	Max. W.P.	⊕	Suction	⊖	Min. Bend Radius	⊕	Wt. Per Ft.	⊕	Standard Pack	Stock (X) or Minimum Order Qty.	Gates Item No.	
Color	(In.)	(mm)	(In.)	(mm)	(psi)	(MPa)	(In. Hg)	(mm Hg)	(In.)	(mm)	(Lbs.)	(Kg)				
Blue	1/4	6.4	.50	12.7	250	1.72	30.0	762	3.0	76	.08	.04	Reel	25,000 ft.	3204-1496	
Blue	3/8	9.5	.66	16.8	250	1.72	30.0	762	3.0	76	.14	.06	Reel	X	3204-1497	
Blue	3/8	9.5	.69	17.5	300	2.07	30.0	762	3.0	76	.15	.07	Reel	25,000 ft.	3204-1501	
Blue	1/2	12.7	.81	20.6	250	1.72	25.0	635	5.0	127	.19	.09	Reel	X	3204-1498	
Blue	1/2	12.7	.83	21.1	300	2.07	25.0	635	5.0	127	.20	.09	Reel	25,000 ft.	3204-1503	
Blue	3/4	19.1	1.15	29.2	250	1.72	20.0	508	6.0	152	.35	.16	Reel	X	3204-1500	
Blue	3/4	19.1	1.15	29.2	300	2.07	15.0	381	6.0	152	.35	.16	Reel	X	3204-1505	
Blue	3/4	19.1	1.15	29.2	300	2.07	15.0	381	6.0	152	.35	.16	50 ft.	200 ft. (X)	3204-0560	
Green	1/4	6.4	.50	12.7	250	1.72	30.0	762	3.0	76	.08	.04	Reel	25,000 ft.	3204-1516	
Green	3/8	9.5	.69	17.5	300	2.07	30.0	762	3.0	76	.15	.07	Reel	25,000 ft.	3204-1511	
Green	3/8	9.5	.66	16.8	250	1.72	30.0	762	3.0	76	.14	.06	Reel	25,000 ft.	3204-1517	
Green	1/2	12.7	.83	21.1	300	2.07	25.0	635	5.0	127	.20	.09	Reel	25,000 ft.	3204-1513	
Green	1/2	12.7	.81	20.6	250	1.72	25.0	635	5.0	127	.19	.09	Reel	25,000 ft.	3204-1518	
Green	3/4	19.1	1.15	29.2	300	2.07	15.0	381	6.0	152	.35	.16	Reel	X	3204-1515	
Green	3/4	19.1	1.15	29.2	250	1.72	20.0	508	6.0	152	.35	.16	Reel	25,000 ft.	3204-1520	
Green	3/4	19.1	1.15	29.2	300	2.07	15.0	381	6.0	152	.35	.16	50 ft.	200 ft. (X)	3204-0506	
Yellow	1/4	6.4	.50	12.7	250	1.72	30.0	762	3.0	76	.08	.04	Reel	25,000 ft.	3204-1526	
Yellow	3/8	9.5	.69	17.5	300	2.07	30.0	762	3.0	76	.15	.07	Reel	25,000 ft.	3204-1521	
Yellow	3/8	9.5	.66	16.8	250	1.72	30.0	762	3.0	76	.14	.06	Reel	25,000 ft.	3204-1527	
Yellow	1/2	12.7	.83	21.1	300	2.07	25.0	635	5.0	127	.20	.09	Reel	25,000 ft.	3204-1523	
Yellow	1/2	12.7	.81	20.6	250	1.72	25.0	635	5.0	127	.19	.09	Reel	X	3204-1528	
Yellow	3/4	19.1	1.15	29.2	300	2.07	15.0	381	6.0	152	.35	.16	Reel	25,000 ft.	3204-1525	
Yellow	3/4	19.1	1.15	29.2	250	1.72	20.0	508	6.0	152	.35	.16	Reel	25,000 ft.	3204-1530	
Yellow	3/4	19.1	1.15	29.2	300	2.07	15.0	381	6.0	152	.37	.17	50 ft.	200 ft. (X)	3204-0558	

RECOMMENDED FOR: Air and water applications requiring maximum flexibility in any industry, including mining, construction, agriculture, vehicle repair and in-plant operations. Outstanding resistance to heat and ozone. Suitable for light agricultural spraying, such as dilute solutions of herbicides.

TEMPERATURE: -40°F to +200°F (-40°C to +93°C) continuous service.

CONSTRUCTION: **Tube:** Type P (EPDM). Black.
Reinforcement: Synthetic, high tensile textile cord.
Cover: Type P (EPDM). Blue, Green or Yellow. All sizes through 1/2" are perforated.
Design Factor: 3:1

COUPLINGS: 19 (up through 1/2" only), 1, 3 or 4, (up through 1/2" with 20 brass ferrules, up through 1" with bands), 72 Gates Power Crimp® or 75 Gates GLX®. Reference the Hose Coupling Section.

PACKAGING: Minimum of 90% of hose reels will be 1-piece lengths.
3/8" through 3/4": Packaged in 500' to 700' reels. Maximum 2 pieces in 50' increments.
3/4" x 50': Packaged 200' per carton, each length coiled and tied.

BRANDING: Continuous ink brand. Example: "GATES® ADAPTA FLEX™ MULTI-PURPOSE 3/8 INCH (9.5mm) 300 PSI (2.07MPa) WP MADE IN USA"

SPECIAL ORDER REQUIREMENTS: Special production runs require minimum order quantities of 25,000 feet per size.

REMNANT LENGTHS: None.

STANDARDS: **Tube:** ARPM (Class C) Limited oil resistance.

ACID-
CHEMICAL

AIR AND
MULTI-
PURPOSE

FOOD AND
BEVERAGE

MARINE

MATERIAL
HANDLING

MINING

OILFIELD

PETROLEUM
TRANSFER

PRESSURE
WASHER

STEAM

WATER

CLAMPS

COUPLINGS
AND
FERRULES

HOSE FINDER

CHEMICAL
RESISTANCE
TABLE



Powering Progress.

gates.com/industrialhose