

SHOT BLAST HOSE

SB2P / SB4P

Product Specifications

Application : Special extra thick tube compound is formulated to extend service life in sandblasting service.

Tube : Black abrasion resistant synthetic rubber

Reinforcement : Spiral-plied synthetic fabric

Cover : Black abrasion, weather & ozone resistant synthetic rubber

Temperature	-20°F to 180°F (-30°C to 80°C)
Safety Factor	4:1
Max. Lengths	200FT / 60m
Abrasion	DIN 100 ~ 130mm ³
Branding	HWASEUNG Exvill SHOT BLAST ---PSI MAX. W.P



Part No.	I.D		O.D		MAX. W.P		Bend Radius		Approx. Weight	
	in	mm	in	mm	psi	bar	in	mm	lbs/ft	kg/m
SB2P										※ Reinforcement : 2PLY
SB2P-102	1"	25.4	1.70	43.2	150	10	-	-	0.77	1.14
SB2P-132	1 1/4"	31.8	1.95	49.6	150	10	-	-	0.91	1.35
SB2P-152	1 1/2"	38.1	2.20	55.9	150	10	-	-	1.05	1.56
SB2P-172	1 3/4"	44.5	2.45	62.3	150	10	-	-	1.19	1.77
SB2P-202	2"	50.8	2.70	68.6	150	10	-	-	1.33	1.98
SB2P-252	2 1/2"	63.5	3.25	82.5	100	7	-	-	1.73	2.57
SB2P-302	3"	76.2	3.75	95.2	100	7	-	-	2.03	3.02
SB4P										※ Reinforcement : 4PLY
SB4P-104	1"	25.4	1.80	45.8	150	10	-	-	0.92	1.37
SB4P-134	1 1/4"	31.8	2.06	52.2	150	10	-	-	1.08	1.60
SB4P-154	1 1/2"	38.1	2.30	58.5	150	10	-	-	1.24	1.84
SB4P-174	1 3/4"	44.5	2.56	64.9	150	10	-	-	1.40	2.08
SB4P-204	2"	50.8	2.80	71.2	150	10	-	-	1.56	2.32
SB4P-254	2 1/2"	63.5	3.35	85.1	150	10	-	-	2.00	2.98
SB4P-304	3"	76.2	3.85	97.8	150	10	-	-	2.34	3.48

PREMIUM SHOT BLAST HOSE

PSB2P / PSB4P

Product Specifications

Application : Designed for sandblasting of metal castings, steel, stone, cement and wherever abrasive materials are carried at high velocity.

Tube : Black high abrasion resistant synthetic rubber

Reinforcement : Spiral-plied synthetic fabric

Cover : Black abrasion, weather & ozone resistant synthetic rubber

Temperature	-20°F to 180°F (-30°C to 80°C)
Safety Factor	4:1
Max. Lengths	200FT / 60m
Abrasion	DIN 70 ~ 90mm ³
Branding	HWASEUNG Exwill PREMIUM SHOT BLAST - - -PSI MAX. W.P



Part No.	I.D		O.D		MAX. W.P		Bend Radius		Approx. Weight	
	in	mm	in	mm	psi	bar	in	mm	lbs/ft	kg/m
PSB2P										※ Reinforcement : 2PLY
PSB2P-102	1"	25.4	1.70	43.2	150	10	-	-	0.75	1.11
PSB2P-132	1 1/4"	31.8	1.95	49.6	150	10	-	-	0.88	1.31
PSB2P-152	1 1/2"	38.1	2.20	55.9	150	10	-	-	1.01	1.51
PSB2P-172	1 3/4"	44.5	2.45	62.3	150	10	-	-	1.16	1.72
PSB2P-202	2"	50.8	2.70	68.6	150	10	-	-	1.29	1.92
PSB2P-252	2 1/2"	63.5	3.25	82.5	100	7	-	-	1.68	2.50
PSB2P-302	3"	76.2	3.75	95.2	100	7	-	-	1.98	2.94
PSB4P										※ Reinforcement : 4PLY
PSB4P-104	1"	25.4	1.80	45.8	150	10	-	-	0.89	1.33
PSB4P-134	1 1/4"	31.8	2.06	52.2	150	10	-	-	1.05	1.57
PSB4P-154	1 1/2"	38.1	2.30	58.5	150	10	-	-	1.21	1.80
PSB4P-174	1 3/4"	44.5	2.56	64.9	150	10	-	-	1.36	2.03
PSB4P-204	2"	50.8	2.80	71.2	150	10	-	-	1.52	2.26
PSB4P-254	2 1/2"	63.5	3.35	85.1	150	10	-	-	1.96	2.91
PSB4P-304	3"	76.2	3.85	97.8	150	10	-	-	2.28	3.40