

DRY CEMENT DISCHARGE HOSE

DC7548 / DC7564
DC15048 / DC15064

Product Specifications

Application : Used in the transfer of dry materials & slurries and ideal for dry cement, pebble, lime and other abrasive materials.

Tube : Black abrasion resistant synthetic rubber

Reinforcement : Spiral-plyed synthetic fabric

Cover : Black abrasion, weather & ozone resistant synthetic rubber

Temperature	-20°F to 180°F (-30°C to 80°C)		
Safety Factor	4:1	Max. Lengths	200FT / 60m
Abrasion	DIN 130 ~ 150mm ³		
Branding	HWASEUNG Exwill DRY CEMENT DISCHARGE - - -PSI MAX. W.P		



Part No.	I.D		O.D		MAX. W.P		Bend Radius		Approx. Weight	
	in	mm	in	mm	psi	bar	in	mm	lbs/ft	kg/m
DC7548 : 3/16" Tube										
DC7548-302	3"	76.2	3.64	92.4	75	5	30	750	1.83	2.72
DC7548-402	4"	101.6	4.64	117.8	75	5	40	1,000	2.37	3.53
DC7548-502	5"	127.0	5.64	143.2	75	5	50	1,300	2.92	4.34
DC7548-602	6"	152.4	6.65	168.8	75	5	60	1,500	3.55	5.28
DC7564 : 1/4" Tube										
DC7564-302	3"	76.2	3.76	95.6	75	5	30	750	2.21	3.29
DC7564-402	4"	101.6	4.76	121.0	75	5	40	1,000	2.86	4.26
DC7564-502	5"	127.0	5.76	146.4	75	5	50	1,300	3.51	5.22
DC7564-602	6"	152.4	6.77	172.0	75	5	60	1,500	4.25	6.32
DC15048 : 3/16" Tube										
DC15048-302	3"	76.2	3.65	92.6	150	10	30	750	1.87	2.79
DC15048-402	4"	101.6	4.76	120.8	150	10	40	1,000	2.83	4.21
DC15048-502	5"	127.0	5.79	147.0	150	10	50	1,300	3.65	5.43
DC15048-602	6"	152.4	6.79	172.4	150	10	60	1,500	4.39	6.53
DC15064 : 1/4" Tube										
DC15064-302	3"	76.2	3.77	95.8	150	10	30	750	2.26	3.37
DC15064-402	4"	101.6	4.88	124.0	150	10	40	1,000	3.33	4.96
DC15064-502	5"	127.0	5.91	150.2	150	10	50	1,300	4.25	6.33
DC15064-602	6"	152.4	6.91	175.6	150	10	60	1,500	5.11	7.60